

BENKA PATCH PANEL CAT 3

APPLICATION

BENKA patch panel Cat 3 exceed standard performance of telephone system and will support the following applications, such as:

- TP-PMD
- ISDN
- ADSL

STANDARDS

ANSI/TIA-568-B.2

ISO/IEC 11801

RoHS



TECHNICAL DATA

General Specifications	
Transmission Standard	ANSI/TIA-568-B.2 ISO/IEC 11801
Cable Type	U/UTP (Unshielded)
Total Ports, Quantity	25 or 50
Color	Black
Label	Write-on Label, Easy to Identify
Package Quantity	1
Packaging Type	Bag
Rack Type	EIA 19 in Rack Units 1.0

Mechanical Specifications	
Panel Style	Straight
Material Type	High-impact, Flame Retardant, Thermoplastic, Steel
Panel Mounting	Flush
Termination Type	IDC
Conductor type	Solid or Stranded
Jack Termination Durability	>750 times
IDC Termination Durability	>250 times
Dust Cover	Optional

PART NUMBER

Part Number	Description
BNK-PPC3U25F1	BENKA Patch Panel, Cat.3 UTP, 25 Port, Flat, 1U
BNK-PPC3U50F1	BENKA Patch Panel, Cat.3 UTP, 50 Port, Flat, 1U