

BENKA COUPLING

APPLICATION

BENKA Coupling-adapter provide a robust solution for LANs, public networks, storage area networks fiber-to-the-desk applications. They have been designed for installation into the BENKA Optical Distribution Frames, and available in duplex SC type, duplex LC type.

STANDARD

ISO 11801, ANSI/TIA- 568-C.3, TIA/EIA-604 (FOCIS)

IEC 60297-3, EIA-310-D

IEC 61754-4, IEC 61300-3-4, IEC 61754-20, IEC 61300-3-4

RoHS



TECHNICAL DATA

General Specifications	
Body Style	Simplex or Duplex
Interface	LC or SC
Interface Feature	Flangeless
Fiber Mode	Single Mode or Multi mode
Connector Color	Beige (MM), Aqua (OM3), Blue (SM)
Operating Temperature	-20°C~75°C

PART NUMBER

Part Number	Description
BNK-CLM3SD	BENKA Coupling OM3 SC Duplex
BNK-CLM3LD	BENKA Coupling OM3 LC Duplex
BNK-CLMSD	BENKA Coupling Single Mode SC Duplex
BNK-CLSMLD	BENKA Coupling Single Mode LC Duplex
BNK-CLSMSS	BENKA Coupling Single Mode SC Simplex